

IHS



Designed and Manufactured in the USA

Industrial Heating Systems

"We control the heat of your chemistries"

DTOT-S or T -3- SERIES

Deep tank heaters are used in tanks over 10 feet deep. The rugged riser comes up and over the tank lip for support.

This series comes in a 316 stainless and titanium design. and yes ... it is all purge welded for the best quality.

This is THE heater for those :
205 F HOT SEAL TANKS on that anodizing line.
180 F MAG PHOSPHATE TANK
160 F CLEANER TANK.
CAUSTIC TANKS
HARD CHROME TANKS WITH NO FLUORIDES

THESE HEATERS ARE DESIGNED TO TAKE THE HEAT!

Used with one our solution level safety devices with the MANUAL RESET BUTTON that keeps the heater from re-energizing once the solution has dropped, or maybe the tank fails, or maybe the recirculation line broke.. what ever the reason.

HEATED LENGTH	APPROXIMATE WATTAGE
44"	24000 W
52"	27000 W
55"	30000 W
60"	33000 W
64"	36000 W
72"	40000 W

These are built for your applications. Protective HEAT SHIELDS ARE RECOMMENDED FOR PLASTIC OR PLASTIC LINED TANKS.

WWW.INDUSTRIALHEATINGSYSTEMS.COM

**9530 W. Bethel Ct. Suite B
Boise, ID 83709
208-323-6143**



INDUSTRIAL HEATING SYSTEMS 9530 W BETHEL CT. UNIT 2
BOISE, ID 83709 PHONE 208-323-6143
IMMERSION TANK HEATERS
Model# DTOT-T-3-644-3S,-36000W/480/3 PH